



Dealer Name
 Joe Salesman
 123 Some Road
 Minneapolis, MN 55555
 612-555-5555

Combine Specification Comparison

	Case IH Case IH 8120	John Deere 9560 STS	New Holland CR9040
Engine			
Type	Iveco	6068HH	Cursor 9
Displacement - cu in (L)	629 (10.3)	414 (6.8)	531 (8.7)
Horsepower - hp (kW)	420 (313)	265 (198)	322 (240)
Power Rise - hp (kW)	43 (32.1)	19 (14.1)	50 (37.3) @ 2000 rpm
Power Boost Unloading - hp (kW)	NA	30 (22.4)	25 (19) @ 2100 rpm
Max Horsepower - hp (kW)	463 (345)	295 (220)	372 (277)
Threshing / Separation			
Type	Rotary CVT Drives	Rotary	Twin Rotary
Rotor Diameter - in (mm)	30 (762)	24 (610) threshing / 27 (686) separating	17 (432)
Concave Modules	2 section, 4 piece bar & wire, slotted	Open, Adj, 3 section	Open, 10 Bar Grain / 7 Bar Corn(2)
Concave Adjustment	Electric	Electro-Mechanical	Electric
Discharge Beater	Available	Std	Std
Grain Loss Monitor	Std	Std	Std
Cleaning System			
Total Cleaning Area - sq in (sq m)	10,075 (6.5)	5,583 (3.602)	8,370 (5.400)
Cleaning Fan	Cross Flow Plus	12 Blade - Scroll Type	6 blade
Self-Leveling Cleaning System	Std	na	Std
Conveying and Storage			
Tailings Elevator	Paddle	Paddle	Single auger with Tailings Processor
Clean Grain Elevator	Paddle	Paddle	Paddle
Grain Tank Capacity - bu (L)	350 (12334)	220 (7800)	315 (11100)
Unloading Auger Length - in (mm)	252 (6401)	222 (5639)	252 (6401)
Unloading Speed - bu/sec (L/sec)	3.2 (113)	2.2 (78)	3.2 (112)
Dimensions			
Wheelbase - in (mm)	149.1 (3787)	138 (3505)	148 (3759)
Base Weight w/Tires - lbs (kg)	36,043 (16349)	27,447 (12450)	34,308 (15562)
Cab Height - in (mm)	153.7 (3904)	156 (3962)	155.5 (3950)
Fuel Tank - gal (L)	277 (1050)	200 (757)	200 (757)